

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,912,035 B2
APPLICATION NO. : 09/754232
DATED : June 28, 2005
INVENTOR(S) : Toshiki Kaneko et al.

Page 1 of 6

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Claims should read as follows:

Col. 17 - 18

1. A liquid crystal display device comprising:
a pair of substrates;
a liquid crystal layer interposed between said pair of substrates;
drain lines and gate lines formed on one of said pair of substrates and crossing each other in a matrix form, each crossing one of said drain lines and gate lines defining a pixel;
a switching element associated with and disposed relative to each pixel;
a sheet like counter electrode comprising a transparent conductive film arranged at each pixel;
a counter voltage line formed on said counter electrode, said counter voltage line including a multi layered structure comprising a first molybdenum layer, an aluminum layer or an alloy layer comprising essentially of aluminum, and a second molybdenum layer in this order;
a first insulating layer formed on said counter electrode and said counter voltage line;
a second insulating layer formed on said first insulating layer; and
a pixel electrode comprising a transparent conductive film which is electrically connected to said switching element.

Col. 18

2. The liquid crystal display device according to claim 1, wherein at least one of said first molybdenum layer and said second molybdenum layer comprises an alloy layer comprising essentially of molybdenum.

Col. 18

3. The liquid crystal display device according to claim 1, wherein said pixel electrode has an approximately linear shaped structure, zigzag shaped structure, slit shape structure, or comb shaped structure.

Col. 18

4. The liquid crystal display device according to claim 3, wherein said pixel electrode extends in the same direction as said gate lines.

Col. 18

5. The liquid crystal display device according to claim 1, wherein said transparent conductive film of said pixel electrode and of said counter electrode each includes one of ITO, IZO and IGO.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,912,035 B2
APPLICATION NO. : 09/754232
DATED : June 28, 2005
INVENTOR(S) : Toshiki Kaneko et al.

Page 2 of 6

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Claims should read as follows: (cont'd)

Col. 18

6. The liquid crystal display device according to claim 5, wherein said transparent conductive film is a polycrystalline.

Col. 18

7. The liquid crystal display device according to claim 5, wherein said transparent conductive film is amorphous.

Col. 18

8. The liquid crystal display device according to claim 5, wherein said transparent conductive film of said pixel electrode and of said counter electrode are different materials.

Col. 18

9. The liquid crystal display device according to claim 8, wherein said transparent conductive film is a polycrystalline.

Col. 18

10. The liquid crystal display device according to claim 8, wherein said transparent conductive film is amorphous.

Col. 18

11. The liquid crystal display device according to claim 1, wherein said switching element is a thin film transistor and said first insulating layer is a gate insulating layer of said thin film transistor.

Col. 18

12. A liquid crystal display device comprising:
a pair of substrates;
a liquid crystal layer interposed between said pair of substrates;
a sheet like first electrode comprising a transparent conductive film arranged on one of said pair of substrates;
a multi layered structure line comprising a first molybdenum layer, an aluminum layer or an alloy layer comprising essentially of aluminum, and a second Molybdenum layer in this order formed on said first electrode;
a first insulating layer formed on said first electrode and said multilayered structure line;
a second insulating layer formed on said first insulating layer; and
a second electrode comprising a transparent conductive film formed on said second insulating layer.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,912,035 B2
APPLICATION NO. : 09/754232
DATED : June 28, 2005
INVENTOR(S) : Toshiki Kaneko et al.

Page 3 of 6

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Claims should read as follows: (cont'd)

Col. 18

13. The liquid crystal display device according to claim 12, wherein at least one of said first molybdenum layer and said second molybdenum layer of multi layered structure line comprises an alloy layer comprising essentially of molybdenum.

Col. 18

14. The liquid crystal display device according to claim 12, wherein said second electrode has an approximately linear shaped structure, zigzag shaped structure, slit shape structure, or comb shaped structure.

Col. 19

15. The liquid crystal display device according to claim 14, wherein said second electrode extends in the same direction as said gate line.

Col. 19

16. The liquid crystal display device according to claim 12, further comprising drain lines and gate lines formed on one of said pair of substrates and crossing each other in a matrix form, pixels being formed corresponding to domains surrounded by crossings of said drain lines and said gate lines, wherein said first electrode and said second electrode are arranged for each pixel.

Col. 19

17. The liquid crystal display device according to claim 16, wherein said transparent conductive film is a polycrystalline.

Col. 19

18. The liquid crystal display device according to claim 16, wherein said transparent conductive film is amorphous.

Col. 19

19. The liquid crystal display device according to claim 16, further comprising a switching element arranged for each pixel, wherein said switching element is connected said second electrode.

Col. 19

20. The liquid crystal display device according to claim 19, wherein said switching element is a thin film transistor and said first insulating layer is a gate insulating layer of said thin film transistor.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,912,035 B2
APPLICATION NO. : 09/754232
DATED : June 28, 2005
INVENTOR(S) : Toshiki Kaneko et al.

Page 4 of 6

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Claims should read as follows: (cont'd)

Col. 19

21. The liquid crystal display device according to claim 16, wherein said multi layered structure line is arranged over two or more pixels.

Col. 19

22. The liquid crystal display device according to claim 21, wherein said multi layered structure line extends in the same direction as said gate lines.

Col. 19

23. The liquid crystal display device according to claim 12, wherein said transparent conductive film of said first electrode and of said second electrode each includes one of ITO, IZO and IGO.

Col. 19

24. The liquid crystal display device according to claim 23, wherein transparent conductive film of said first electrode and said second electrode are different materials.

Col. 19

25. The liquid crystal display device according to claim 24, wherein said transparent conductive film is a polycrystalline.

Col. 20

26. The liquid crystal display device according to claim 24, wherein said transparent conductive film is amorphous.

Col. 20

27. The liquid crystal display device according to claim 23, wherein said transparent conductive film is a polycrystalline.

Col. 20

28. The liquid crystal display device according to claim 23, wherein said transparent conductive film is amorphous.

Col. 20

29. The liquid crystal display device according to claim 1, wherein said transparent conductive film of said counter electrode includes one of ITO, IZO and IGO.

Col. 20

30. The liquid crystal display device according to claim 29, wherein said transparent conductive film is polycrystalline.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,912,035 B2
APPLICATION NO. : 09/754232
DATED : June 28, 2005
INVENTOR(S) : Toshiki Kaneko et al.

Page 5 of 6

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Claims should read as follows: (cont'd)

Col. 20

31. The liquid crystal display device according to claim 29, wherein said transparent conductive film is amorphous.

Col. 20

32. The liquid crystal display device according to claim 1, wherein said counter voltage line extends in the same direction as said gate lines,

Col. 20

33. The liquid crystal display device according to claim 30, wherein said counter voltage line extends in the same direction as said gate lines.

Col. 20

34. A liquid crystal display device comprising:
a pair of substrates;
a liquid crystal layer interposed between said pair of substrates;
drain lines and gate lines formed on one of said pair of substrates and crossing each other in a matrix form, each crossing one of said drain lines and gate lines defining a pixel;
a switching element associated with and disposed relative to each pixel;
a sheet like counter electrode comprising a transparent conductive film arranged at each pixel;
a counter voltage line formed on said counter electrode, said counter voltage line including a multi layered structure comprising a first molybdenum-containing layer, an aluminum layer or an alloy layer comprising essentially of aluminum, and a second molybdenum-containing layer in that order;
a first insulating layer formed on said counter electrode and said counter voltage line;
a second insulating layer formed on said first insulating layer; and
a pixel electrode comprising a transparent conductive film which is electrically connected to said switching element,
wherein said first molybdenum-containing layer is either a layer of molybdenum or an alloy layer comprising essentially of molybdenum,
wherein said second molybdenum-containing layer is either a layer of molybdenum or an alloy layer comprising essentially of molybdenum.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,912,035 B2
APPLICATION NO. : 09/754232
DATED : June 28, 2005
INVENTOR(S) : Toshiki Kaneko et al.

Page 6 of 6

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Claims should read as follows: (cont'd)

Col. 20

35. A liquid crystal display device comprising:

a pair of substrates;

a liquid crystal layer interposed between said pair of substrates;

a sheet like first electrode comprising a transparent conductive film arranged on one of said pair of substrates;

a multi layered structure line comprising a first layer containing molybdenum, an aluminum layer or an alloy layer comprising essentially of aluminum, and a second layer containing molybdenum, in that order formed on said first electrode;

a first insulating layer formed on said first electrode and said multilayered structure line;

a second insulating layer formed on said first insulating layer; and


a second electrode comprising a transparent conductive film formed on said second insulating layer,

wherein said first layer is either a layer of molybdenum or an alloy layer comprising essentially of molybdenum,

wherein said second layer is either a layer of molybdenum or an alloy layer comprising essentially of molybdenum.

Signed and Sealed this

Seventh Day of August, 2007



JON W. DUDAS
Director of the United States Patent and Trademark Office